



40 DL-B



Order No. 310 003
Synchronous alternator
Stamford BCI 184 J

Engine type DEUTZ B4M 2011
Turbo, oil-cooled

Standard outfit

- 1 x Schuko 230 V/16 A
- 2 x CEE 230 V/16 A
- 1 x CEE 400 V/32 A
- 1 x CEE 400 V/63 A
- Analogue, manual switchpanel with control units
- Thermo magnetic automatic circuit breaker with 3-pole protection
- FI protection switch
- Crane handling device
- Optical tank gauge

Specifications

| | |
|--------------------------------------|----------------------------|
| Max. output [LTP] kVA/kW | 41,2/33,0 |
| Prime power [PRP] kVA/kW | 39,3/31,4 |
| Building class/Isolation | Synchronous/Class H |
| Nominal voltage | 400 V 3~/230V 1~ |
| Nominal current/cos (phi) | 56,7 A 3~/0,8 |
| Frequency | 50 Hz |
| Regulation | electronic (+- 1,5) |
| Engine version | 4 Cylinder 4-stroke diesel |
| Engine capacity | 3110 cm ³ |
| Constant power [PHP] | 36,4 kW |
| RPM/Regulation | 1500/mechanical |
| Fuel / Tank capacity (litres) | Diesel/51 |
| Consumption/Running-time*1 | 7,1l/7 h |
| Cooling air volume m ³ /h | 2370 |
| Start-up system/Battery V/Ah | E-Start 3 kW/12/70 |
| Sound power level LWA*3 | 92 dB(A) |
| Sound pressure level LPA*2 | 67 dB(A) |
| Weight approx. kg | 918 |
| Dimensions L x W x H in mm | 2000 x 920 x 1300 |

Steuernummer: 310/5113/1083 || Ust.-ID: DE 209435443
Bankverbindung: Sparkasse Herford || BLZ: 49450120
Kontonummer: 102156346
Swift-BIC WLAHDE44XXX || IBAN DE 59494501200120156346

Dipl.-Ing. Holger Roswandowicz || Werfener Heide 14
32257 Bünde
Tel. 05223 1800 939 || Fax. 05223 1800 947
Mail: info@bhkw-beratung.com || WEB www.bhkw-anlagen.com



| Special Equipment(not retrofit) | Order No. |
|--|---|
| Automatic control panel | 342 400 incl. pre-heating-system, 1 x CEE 400 V |
| Electronic engine speed governor | 342 001 |
| Available accessories | |
| Load transfer switch | 343 002/E-US 60 |
| Earth rod | 342 304 |
| Trailer according to StVZO: | |
| One axle trailer FG 135 ST | 341 102 |
| One axle trailer FG 135 HV | 341 103 |
| DIN pull eyelet 40 mm für LKW | 341 501 for FG 135 HV |
| Rear parking supports, (1 pair) | 341 500 |
| Supporting wheel, semi automatic, strengthened | 341 502 |

***1 Consumption in litres per hour, running time in hours. This specification is given at 3/4 load and therefore is non-binding. *2 Noise level declaration based on directive 2000/14/EG. *3 Noise level at 7m.**

ST = rigid drawbar, HV = height adjustable drawbar