

404 YS-GT ISO Diesel



Order No. 122 001
Synchronous alternator

Engine type Yanmar L 70

Standard outfit

1 x Schuko 230 V/16 A,
1 x CEE 230 V/16 A,
1 x CEE 230 V/32 A,
Overload protection,
Voltmeter,
Isometer

Application areas*

| | |
|--|--------|
| Electric tools up to | 2800 W |
| Gardening and construction equipment up to | 1900 W |
| Compressors, pumps up to | 1500 W |

230 V

*As the power needs of each consumer are influenced by various factors, no claims can be derived from this table.

Specifications

| | |
|----------------------------------|---------------------|
| Max. output [LTP] kVA/kW | 3,8/3,4 |
| Prime Power [PRP] kVA/kW | 3,2/2,9 |
| Nominal voltage | 230 V 1~ |
| Nominal current | 13,9 A 1~ |
| Efficiency factor cos (phi) | 0,9 |
| Frequency / Type of protection | 50 Hz/IP 23 |
| Engine version | 1 Cylinder 4-stroke |
| Engine capacity | 296 cm ³ |
| Power at 3000 rpm | 4,8 kW/6,5 HP |
| Fuel / Tank capacity (litres) | Diesel/18 |
| Running-time at 3/4 load approx. | 18 h |
| Start-up system | Recoil |
| Sound power level LWA | 96 dB(A) |
| Sound pressure level (7 m) | 71 dB(A) |
| Weight approx. kg | 98 |
| Dimensions L x W x H in mm | 800 x 520 x 660 |
| Available accessories | Order No. |
| Set of wheels with handles | 161 000 |
| Carrying handles fold-out | 161 002 |